

HotMelt™

- Plotter-cut adhesive for use with our Textile Foils, Flocking Sheets, and Reflective Sheets
- Comes with no liner and a clear carrier
- Makes weeding detailed designs much easier

Clear SMCCH-100

Acceptable Fabrics

Cotton, Uncoated Polyester, Cotton/Polyester Blends, Polyester/Acrylic
Excluding Nylon

Sizing Available

Available Widths (in.): 20" only

Available Lengths (ft.): 15', 30', 45', 60, 90, and 162' rolls

Thickness

2.4 mils/60 microns



**QUALITY DIGITAL
SOLUTIONS**

#12, 5815 - 40 Street S.E.
Calgary, Alberta, T2C 2H6



403.262.6915 888.235.2838
qualitydigitalsolutions.ca



No longer
has a liner



45° Blade
with very
low pressure



Cut this material in
mirror image with the
smooth side down



300°F



Medium,
even pressure



5 Seconds



Peel warm,
almost hot



Place foil over the Hotmelt,
cover with Teflon Sheet &
press for 10 seconds. Let
cool completely, then peel.



Wash inside out,
cold water, line dry.
Not suitable for
dry-cleaning.

SpecialtyMaterials.com | 877.437.8556

**Specialty
Materials™**

Test on dazzle cloth and other moisture-wicking polyesters. Moisture-wicking materials have better adhesion when washed and dried using no fabric softener or blotted with rubbing alcohol before pressing. Be advised that dye migration has occurred with low energy dyes in polyester and poly-blend fabrics. All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability, whatsoever, in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

Copyright © 2021, Specialty Materials & Digital Decoration, LLC. All rights reserved. Tulsa, OK 74107 | 866-437-8599