

LOVE what you **PRESS!**

REFLECTION PROTECTIO

REFLECTIVE HEAT TRANSFER FILM

PLEASE NOTE: NEW APPLICATION INSTRUCTIONS

Safety Silver RF-9501

Applications

Nylon and other heat sensitive fabrics.



60° Blade Slow cutting speed

3 - 5 seconds



Remove heat liner. Cut this material in mirror image



Peel cold, then cover with Teflon & repress for 10-15 seconds. let cool then remove Teflon



320°F





Wash inside out. Warm water, gentle cycle. Tumble dry low heat. Suitable for dry-cleaning.

Test on dazzle cloth, shiny polyester or moisture-wicking materials.



Safety Silver RF-9505

Applications

Cotton and Cotton-Blend Fabrics



60° Blade Slow cutting speed



Remove heat liner. Cut this material in mirror image



275°F - 305°F



Firm even pressure



3 - 5 seconds



Peel cold, then cover with Teflon & repress for 10-15 at 300°F - 305°F seconds, let cool, remove Teflon



Wash inside out. Warm water, gentle cycle. Tumble dry low heat.

No nylon, dazzle cloth, shiny polyester, or moisture-wicking materials.

Technical Support: Toll Free: 877-437-8556 | SpecialtyMaterials.com

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.