

The **MUTOH XpertJet 1641SR Pro II** 64" eco-solvent printer delivers exceptional quality, increased speed, and improved efficiency at an affordable price. The newly-developed MUTOH **AccuFine HD Pro** printhead ensures flawless dot placement and faster production (up to 60% over the previous model), while improved drying technology unlocks print speeds to their full potential. Additionally, an advanced smart take-up unit comes standard, giving users peace of mind when printing long jobs.

The natural choice for businesses ready to scale, the **XpertJet 1641SR Pro II** maintains MUTOH's made-in-Japan reputation for reliability and quality.



& powered by these MUTOH systems:













WRAPS



SIGNAGE



DECALS



BANNERS



XpertUet 1641SR ProII

Faster. Better. Smarter.




<u>NEW</u> PRINTHEAD (60% FASTER*)

<u>NEW</u> DRYER (20% IMPROVED*)

SMART TAKE-UP (AUTO MOTOR STOP)

XPJ FEATURES
DROPMASTER2
i-SCREEN EFFECTS
FEEDMASTER
MEDIA TRACKER
NOZZLE SELECTION



















Enhance your printing capabilities with the award-winning MUTOH VerteLith™ RIP Software and a complimentary one-year subscription to SAi Flexi DESIGN MUTOH Edition—a combined value of \$1,600.

MUTOH MS41 Eco-Solvent Inks are UL GREENGUARD Gold certified with up to three-year outdoor durability (unlaminated).

		PRINTER SPECIFICATIONS
Printhead	Print Method	On-demand piezo drive system
	Printhead Height	Low1: 1.5mm / Low2: 2.0mm / Middle: 2.5mm / High: 4.0mm
	Number	1 (MUTOH AccuFine HD Pro)
Media	Roll Media Width	Maximum: 63.97in (Minimum: 19.68in)
	Max. Media Thickness	1.0mm or less
	Roll Diameter	Φ7.87in or less
	Core Diameter	2in or 3in cores
	Max. Roll Weight	30kg/66lbs or less
Maximum Printable Width		63.58in
Ink	Туре	Eco-solvent Ink (MS41)
	Color	4 Color - CMYK
	Capacity	1000ml ink bag
Print Resolution		900x1800dpi
Interface		Gigabit-Ethernet (1000BASE-T) - Recommend CAT6+
Power Supply		AC100V-120V±10% (90V-132V) or 200V-240V±10% (180V-264V), Frequency: 50/60 Hz ± 1Hz
Environmental Conditions	Printer Operation	Temperature 68-89°F, Humidity 40%-60%RH (no condensation)
	Ideal Quality	Temperature 72-86°F, Humidity 40%-60%RH (no condensation)
Power Consumption		Operation: 812.0W or less (peak: 2.3kW), Standby: 52.0W or less, Power off: 4.0W or less
External Dimensions		W 109.0in x D 35.2in x H 63.4in (with 1,000ml ink case installed)
Printer Weight		381.4lbs (Printer body: 310.8lbs, Stand: 70.5lbs)
RIP Software		VerteLith (MUTOH genuine RIP software)

^{*}In comparison to the XpertJet 1641SR Pro.