

# Specialty Materials™



THE BEST GARMENT DECORATION PRODUCTS

# LOVE what you PRESS!



## EconomyFlex™

- Thicker film for polyester mesh & polyester jersey athletic uniforms
- Manufactured without pressure-sensitive carrier for easy stacking
- Great for names and numbers due to being easy to cut and weed
- Produce various finishes by using different repressing techniques

 Black EF-01	 White EF-02	 Red EF-03	 Athletic Gold EF-04	 Navy EF-05	 Grey EF-06	 Sky Blue EF-07
 Kelly Green EF-08	 Royal Blue EF-09	 Ath. Dark Gold EF-10	 Orange EF-11	 Purple EF-12	 Brown EF-13	 Pink EF-14
 Crimson EF-15	 Gold EF-16	 Silver EF-17	 Neon Yellow EF-18	 Neon Orange EF-19	 Neon Pink EF-20	 Neon Green EF-21
 Neon Blue EF-22	 Lemon Yellow EF-23	 Dark Green EF-24	 Light Green EF-25	 Aqua EF-26	 Hot Pink EF-28	

\*Cannot be layered

Technical Support: Toll Free: 877-437-8556 | [SpecialtyMaterials.com](http://SpecialtyMaterials.com)

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

Copyright © 2012, Specialty Materials & Digital Decoration, LLC. All rights reserved. 2929 W. 21st Street, Tulsa, OK 74107



For a full matte finish,  
do not repress.

For a satin finish, repress  
with a siliconized sheet  
for 5 seconds.

For a glossy finish, repress  
for 5 seconds with a Teflon  
Sheet.

## Applications

Cotton, Uncoated Polyester, Mesh, and Poly-blend fabrics



45° Blade



Cut this  
material in  
mirror image



330°F



Medium,  
even  
pressure



10 - 15  
seconds



Peel warm  
or cold



Machine wash  
cold, line dry

**No nylon, dazzle cloth, or shiny polyester. These materials cannot be layered. Be advised that dye migration has occurred with low energy dyes in polyester and poly-blend fabrics.**

### \*Instructions for application to moisture-wicking fabrics:

Damp a cloth with rubbing alcohol (isopropyl alcohol), then gently apply it to the area on the garment you want to apply your design. Allow it to dry and apply your material. This will allow better adhesion to the garment.

### \*Instructions for application to dazzle cloth & shiny polyester fabrics:

We highly recommend that you TEST prior to doing large runs. Coated polyester can routinely cause adhesion issues.

**This is a PVC product, which emits hazardous fumes when cut with a laser machine!**

**Technical Support: Toll Free: 877-437-8556 | [SpecialtyMaterials.com](http://SpecialtyMaterials.com)**

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

Copyright © 2012, Specialty Materials & Digital Decoration, LLC. All rights reserved. 2929 W. 21st Street, Tulsa, OK 74107