

SpecialtyPSV™ Fashion Patterns

We have taken our most popular patterns and turned them into high-quality sticker material




Jigsaw Autism
PSV-AUT 01



Small Tie Dye
PSV-STD 01



Rainbow Splash
PSV-RSP 01



Rainbow Fur
PSV-RFR 01



Serape
PSV-SER 01



Pastel Flowers
PSV-PFL 01



Paisley
PSV-PSL 01



Paisley 2
PSV-PSL 02



Sunflower
PSV-SFL 01



Leopard
PSV-LEO 01



Colored Marijuana
PSV-HMP COL



Green Marijuana
PSV-HMP GRN



Graffiti
PSV-GRF 01



Colorful Hearts
PSV-VAL 05



Paint Splatter Black
PSV-SPL BLK



Paint Splatter White
PSV-SPL WHT



Purple Camo
PSV-CAM PUR



Green Camo
PSV-CAM 01



Baseball
PSV-BBL 01



Softball
PSV-SBL YLW



Brown Leather
PSV-LEA BRO



Sugar Skulls
PSV-SSK 01



Black/Orange Slime
PSV-SLM BLO



Ghosts
PSV-HAL 01



Spiderwebs
PSV-HAL 02



Halloween
PSV-HAL 03



Skulls
PSV-SKL BLK



Eyes
PSV-EYE BLU



Bloody Hands
PSV-BLH RED



Zombie Brains
PSV-ZMB GRN



Buffalo Plaid Red
PSV-PLD 01



Awareness 1
PSV-BCA 01



Awareness 2
PSV-BCA 02



Awareness 3
PSV-BCA 03



New Benjamin
PSV-BENJ 01



American Flag
PSV-FP-USA 01



Star
PSV-FP-USA 02



USA Camo
PSV-FP-USA 03



American Flag 2
PSV-FLG 02



American Flag
Distressed
PSV-FLG DTY



American Stars
PSV-AST 01



QUALITY DIGITAL SOLUTIONS

#12, 5815 - 40 Street S.E.
Calgary, Alberta, T2C 2H6



403.262.6915 888.235.2838
qualitydigitalsolutions.ca



SpecialtyMaterials.com | 877.437.8556

Specialty
Materials™

Test on dazzle cloth and other moisture-wicking polyesters. Moisture-wicking materials have better adhesion when washed and dried using no fabric softener or blotted with rubbing alcohol before pressing. Be advised that dye migration has occurred with low energy dyes in polyester and poly-blend fabrics. All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability, whatsoever, in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

Copyright © 2022, Specialty Materials & Digital Decoration, LLC. All rights reserved. Tulsa, OK 74107 | 866-437-8599

SpecialtyPSV™ Fashion Patterns

Acceptable Surfaces

Applies to most clean, dry, hard surfaces, such as metal, wood, glass, ceramic, acrylic, etc. Customize decals for cars, windshields, windows and doors, wine bottles and glasses, laptops, cell phones, makeup boxes, etc. - the possibilities are endless.

Special Precautions

Not suitable for heat transfer. Can be laminated with an approved latex ink lamination film or liquid for added durability. All PSV products, with the exception of Chalkboard, contain PVC and cannot be cut with a laser. PVC emits hazardous fumes when laser cut.

Outdoor Durability: UV, Water, Chemical, & Scratch Resistant

- no lamination: up to 3 years
- with latex approved film lamination: up to 5 years
- indoor in window (no lamination): up to 5 years
- indoor away from direct sunlight (no lamination): up to 200 years

Sizing Available

Rolls: 12" only | Lengths: 15', 30', & 60'
 Sheets: 12" x 15" - Single Sheets & 10 Packs

TRANSFER TAPES

Name	Tackiness	Opacity	Liner	Size Available
AT-160	Medium	Transparent	No Liner	Width: 6" and 12" Length: 60'
AT-160G (Grid)	Medium	Transparent with a grid	No Liner	Width: 6" and 12" Length: 60'
Transfer & Seal Tape	Medium	Opaque	No Liner	Width: 12", 16", and 24" Length: 60'



45° Blade Recommended



Perform a test cut. Cut this material in "right-reading". Be careful not to cut through the paper backing.



Use our AT-160, AT-160G or T&S Tape to transfer your design to a clean surface.



These are microwave and dishwasher safe after a 24 hour curing process.



SpecialtyMaterials.com | 877.437.8556



Test on dazzle cloth and other moisture-wicking polyesters. Moisture-wicking materials have better adhesion when washed and dried using no fabric softener or blotted with rubbing alcohol before pressing. Be advised that dye migration has occurred with low energy dyes in polyester and poly-blend fabrics. All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability, whatsoever, in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

Copyright © 2022, Specialty Materials & Digital Decoration, LLC. All rights reserved. Tulsa, OK 74107 | 866-437-8599